

BEST IN CLASS FOR:**WOOD BASED PANELS:**

PB/SPB

OSB/LSB/FOSB

MDF/HDF

VIBRATING SIFTER

VM100

TO ASSESS THE PERCENTAGE OF THE VARIOUS GRANULOMETRIES PRESENT IN THE MATERIAL



Electro-magnetic impulse operated Sifter, controlled by a separate micro-processor with the following functions:

- Sifting time can be set from 0 to 20 minutes
- Variable vibrating intensity
- Continuous or adjustable intermittent sifting mode.

The vibrating action combines three different types of movement (vertical-lateral-rotational), making this vibrating sifter extremely efficient and reliable. It can house up to twelve sieves with a diameter of 200 mm inclusive of the bottom and lid, or ten 300 mm diameter sieves with bottom and lid.

TECHNICAL DATA

ABSORBED POWER	450 W
ELECTRICAL POWER SUPPLY (SINGLE PHASE)	110/230 V 50/60 Hz
DIMENSIONS (Ø x h)	450 x 1200 mm
SIEVE DIAMETERS AVAILABLE	200 - 300 mm
MAX NUMBER OF SIEVES WHICH MAY BE FITTED	11
VIBRATIONS PER MINUTE	max 3000 N°/min