



CIRCULAR EXTRACTORS

EXTRACON

BEST IN CLASS FOR:



WOOD BASED PANELS:
MDF/HDF
PB/SPB
OSB/LSB/FOSB
INSULATION BOARDS



PRESSED WOOD PACKAGING:
PALLET BLOCKS



PELLETS & ENERGY:
WOOD PELLETS AND
BLACK PELLETS


TECHNICAL FEATURES

- One or two spiral shafts are mounted according to the extraction requirements
- For high production capacity, the machines normally have robust beams able to support the screw shafts on their extremities
- In the case of applications with particularly abrasive materials, we provide technologically advanced wear-resistant coverings applied to the transport surface of the spirals, on the areas concerning tubing and on the crumbling teeth fitted on the periphery of the screws.



BENEFITS

- High extraction capacities with minimum power requirement
- Constant and uniform extraction even in the presence of fibrous and compacted material and without separating them
- Absence of any spontaneous flows inside the discharge hopper
- Routine maintenance can be carried out even on the full silo
- Suitable for silos up to 12 m diameter.

VERSIONS WITH SUPPORT BEAMS FOR THE SCREWS:



VERSIONS WITH CANTILEVERED SCREWS AND WITHOUT SUPPORTING BEAMS:



FOR DRY MATERIAL ONLY:
AF = FIRE-EXTINGUISHING SYSTEM
AE = EXPLOSION VENTS

EXTRACTING SCREW
M1 = ELECTRIC MOTOR
ROTATING TURRET
M2 = MOTOR: HYDRAULIC OR ELECTRIC
M3 = HYDRAULIC POWER PACK MOTOR

VERSIONS WITH SUPPORT BEAMS FOR THE SCREWS

THROUGHPUT UP TO m ³ /h	SCREWS		OVERALL DIMENSIONS mm		WEIGHT APPROX. kg
	D mm	D2 mm	H mm		
Up to 650 m ³ /h	300 - 800	4000 - 10000	UP TO 25000		According to machine dimensions

VERSIONS WITH CANTILEVERED SCREWS AND WITHOUT SUPPORTING BEAMS

THROUGHPUT UP TO m ³ /h	SCREWS		OVERALL DIMENSIONS mm		WEIGHT APPROX. kg
		D mm	D2 mm	H mm	
Up to 200 m ³ /h	1 - 2	220 - 600	4000 - 10000	UP TO 25000	According to machine dimensions